DIALOG(R) File 351: Derwent WPI

(c) 2005 Thomson Derwent. All rts. reserv.

008334765

WPI Acc No: 1990-221766/199029

XRAM Acc No: C90-095793 XRPX Acc No: N90-171973

polyEpoxy resin compsn. for sealing semiconductor - including e.g. reaction prod. of organopolysiloxane with terminal epoxy cpds. and aminosilane

Patent Assignee: TORAY IND INC (TORA )

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
JP 2151622 A 19900611 JP 88307103 A 19881205 199029 B
JP 2591124 B2 19970319 JP 88307103 A 19881205 199716

Priority Applications (No Type Date): JP 88307103 A 19881205

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

JP 2591124 B2 6 C08L-063/00 Previous Publ. patent JP 2151622

Abstract (Basic): JP 2151622 A

Epoxy resin compsn. comprises (A) epoxy resin. (B) a curing agent, (C) modified organopolysiloxane, i.e., reaction product of (C1) organopolysiloxane having epoxy gps. at both terminals with aminosilane and/or reaction prodt of (C2) organopolysiloxane contg. polyalkyleneoxide at the side chain with aminosilane, and (D) silica.

Specially The chemical equivalent ratio of resin (A) to component (B) is 1:0.5.5-1.5, pref. 1:0.7-1.3. The content of (B) is 1-20 1-20, pref. 2-15 wt % in the compsn. The content of (D) is 65-85 wt % in the epoxy resin compsn. The equivalent ratio of aminosilane to (C1) or C2) is 1:0.9-02, pref., 1:0.7-0.5. The compsn. opt. contains a curing promoter, a releasing agent, a coupling agent, a flame-retarder a colouring agent, etc.

USE/ADVANTAGE - The epoxy resin compsn, has low bending modulas of elasticity and good low stress and hardly causes cracking and burr.. The compsn. has good printing properties. The semiconductor sealed with the resin compsn has improved reliability

Title Terms: POLYEPOXIDE; RESIN; COMPOSITION; SEAL; SEMICONDUCTOR; REACT; PRODUCT; ORGANO; POLYSILOXANE; TERMINAL; EPOXY; COMPOUND; AMINO; SILANE Derwent Class: A21; A85; L03; U11

International Patent Class (Main): C08L-063/00

International Patent Class (Additional): C08G-059/17; C08G-059/18;
C08K-003/36; C08L-083/04; H01L-023/29; H01L-023/31; C08L-063/00;
C08L-083-04

File Segment: CPI; EPI